

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DEX QM MOTOR 15W-40
Product code : DX-1540
Type of product : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Industrial use, Professional use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Dex Oil
Galvanibaan 2
NL- 3439 MG Nieuwegein
info@dex-oil.com

1.4. Emergency telephone number

Emergency number : +31(0)10-7420822

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards which do not result in classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	≥ 55 – < 75	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 1 – < 10	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551-76	≥ 1 – < 5	Aquatic Chronic 4, H413
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-16	≥ 1 – < 5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	≥ 0,1 – < 3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	≥ 0,1 – < 3	Not classified
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080-42	≥ 0,1 – < 3	Asp. Tox. 1, H304
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	≥ 0,3 – < 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	(6,25 ≤C < 100) Skin Irrit. 2, H315 (10 ≤C < 12,5) Eye Irrit. 2, H319 (12,5 ≤C < 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Eliminate all ignition sources if safe to do so.
Emergency procedures	: Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

6.2. Environmental precautions

Avoid release to the environment.

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage temperature	: 45 °C
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
OEL STEL	10 mg/m ³ Form: mist
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³ Form: aerosol
NPK-P (OEL C)	10 mg/m ³ Form: aerosol
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1 mg/m ³ Form: mist and particles
Estonia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	5 mg/m ³ Form: mist
France - Occupational Exposure Limits	
VME (OEL TWA)	5 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	5 mg/m ³
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³ Form: mist
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm Form: inhalable fraction
Italy - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³ Form: mist
TPRV (OEL STEL)	3 mg/m ³ Form: mist
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³ Form: mist
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³ Form: Inhalable fraction
Portugal - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: inhalable fraction
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	1 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL TWA) [2]	5 ppm Form: liquid aerosol, fumes
NPHV (OEL STEL)	3 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL STEL) [ppm]	15 ppm Form: liquid aerosol, fumes
Slovenia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	5 mg/m ³ Form: mist
VLA-EC (OEL STEL)	10 mg/m ³ Form: mist

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³ Form: mist and fume
KTV (OEL STEL)	3 mg/m ³ Form: mist and fume
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m ³
Iceland - Occupational Exposure Limits	
OEL TWA	1 mg/m ³ Form: particulates
Norway - Occupational Exposure Limits	
Grønseverdi (OEL TWA) [1]	1 mg/m ³ Form: mineral oil particles
Grønseverdi (OEL TWA) [2]	50 mg/m ³ Form: vapor
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	5 mg/m ³ Form: inhalable fraction
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³
ACGIH OEL STEL	10 mg/m ³
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³
ACGIH OEL STEL	10 mg/m ³
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³ ACGIH TLV (inhalable fraction)
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
OEL STEL	10 mg/m ³ Form: mist
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³ Form: aerosol
NPK-P (OEL C)	10 mg/m ³ Form: aerosol
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1 mg/m ³ Form: mist and particles
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	8 mg/m ³ Form: mist
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³ Form: mist

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm Form: inhalable fraction
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³ Form: mist
TPRV (OEL STEL)	3 mg/m ³ Form: mist
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³ Form: mist
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³ Form: inhalable fraction
Portugal - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: inhalable fraction
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	1 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL TWA) [2]	5 ppm Form: liquid aerosol, fumes
NPHV (OEL STEL)	3 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL STEL) [ppm]	15 ppm Form: liquid aerosol, fumes
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	5 mg/m ³ Form: mist
VLA-EC (OEL STEL)	10 mg/m ³ Form: mist
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³ Form: mist and fume
KTV (OEL STEL)	3 mg/m ³ Form: mist and fume
Iceland - Occupational Exposure Limits	
OEL TWA	1 mg/m ³ Form: particulates
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	1 mg/m ³ Form: mineral oil particles
Grenseverdi (OEL TWA) [2]	50 mg/m ³ Form: vapor
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	5 mg/m ³ Form: inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
MAK (OEL STEL)	10 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
OEL STEL	10 mg/m ³ Form: mist
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	5 mg/m ³
KGVI (OEL STEL)	10 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³ Form: aerosol
NPK-P (OEL C)	10 mg/m ³ Form: aerosol
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1 mg/m ³ Form: mist and particles
Estonia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	5 mg/m ³ Form: mist
France - Occupational Exposure Limits	
VME (OEL TWA)	5 mg/m ³
VLE (OEL C/STEL)	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	5 mg/m ³
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³ Form: mist
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm Form: inhalable fraction
Italy - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³ Form: mist
TPRV (OEL STEL)	3 mg/m ³ Form: mist

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³ Form: mist
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³ Form: Inhalable fraction
Portugal - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: inhalable fraction
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	1 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL TWA) [2]	5 ppm Form: liquid aerosol, fumes
NPHV (OEL STEL)	3 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL STEL) [ppm]	15 ppm Form: liquid aerosol, fumes
Slovenia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	5 mg/m ³ Form: mist
VLA-EC (OEL STEL)	10 mg/m ³ Form: mist
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³ Form: mist and fume
KTV (OEL STEL)	3 mg/m ³ Form: mist and fume
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m ³
WEL STEL (OEL STEL)	10 mg/m ³
Iceland - Occupational Exposure Limits	
OEL TWA	1 mg/m ³ Form: particulates
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	1 mg/m ³ Form: mineral oil particles
Grenseverdi (OEL TWA) [2]	50 mg/m ³ Form: vapor
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	5 mg/m ³ Form: inhalable fraction
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: mist
OEL STEL	10 mg/m ³ Form: mist

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³ Form: aerosol
NPK-P (OEL C)	10 mg/m ³ Form: aerosol
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1 mg/m ³ Form: mist and particles
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	5 mg/m ³ Form: Mist
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³ Form: Mist
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³ Form: Mist
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm Form: Inhalable fraction
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³ Form: mist
TPRV (OEL STEL)	3 mg/m ³ Form: mist
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³ Form: mist
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³ Form: Inhalable fraction
Portugal - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	1 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL TWA) [2]	5 ppm Form: liquid aerosol, fumes
NPHV (OEL STEL)	3 mg/m ³ Form: liquid aerosol, fumes
NPHV (OEL STEL) [ppm]	15 ppm Form: liquid aerosol, fumes
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	5 mg/m ³ Form: mist
VLA-EC (OEL STEL)	10 mg/m ³ Form: mist
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³ Form: mist and fume
KTV (OEL STEL)	3 mg/m ³ Form: mist and fume

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Iceland - Occupational Exposure Limits	
OEL TWA	1 mg/m ³ Form: particulates
Norway - Occupational Exposure Limits	
Grænseverdi (OEL TWA) [1]	1 mg/m ³ Form: mineral oil particles
Grænseverdi (OEL TWA) [2]	50 mg/m ³ Form: vapor
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	5 mg/m ³ Form: Inhalable fraction
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes)	0.7	3 (> 0.65)	EN ISO 374
	Polyvinylchloride (PVC)	2 (> 30 minutes)	0.4	3 (> 0.65)	EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: < -33 °C ASTM D7346
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 224 °C ASTM D92
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 117 mm ² /s @40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 869 kg/m ³ @15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (mg/l)	> 5000 mg/l/4h
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h 403 Acute Inhalation Toxicity Test

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LD50 oral (rat)	> 2000 mg/kg OECD Test Guideline 401
LD50 dermal (rat)	> 2000 mg/kg OECD Test Guideline 402

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

LD50 oral (rat)	2600 mg/kg bw/day Tested according to Annex V of Directive 67/548/EEC
LD50 dermal (rabbit)	> 3160 mg/kg bodyweight OECD Test Guideline 402
LC50 inhalation (rat) (mg/l)	> 2 mg/l (1h) - OECD403

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rat)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 2,18 mg/l/4h

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h 403 Acute Inhalation Toxicity Test

Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5 mg/l/4h
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h 403 Acute Inhalation Toxicity Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)	
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
Aspiration hazard	: Not classified
DEX QM MOTOR 15W-40	
Viscosity, kinematic	117 mm ² /s @40°C (ASTM D7042)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	98 (98 – 108) mm ² /s @40°C
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)	
Viscosity, kinematic	3050 mm ² /s @40°C
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Viscosity, kinematic	1,99 – 847 mm ² /s Temp.: '40°C

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Viscosity, kinematic	150 (1,99 – 847) mm ² /s @40°C
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	
Viscosity, kinematic	19 mm ² /s @40°C
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Viscosity, kinematic	1,99 – 847 mm ² /s 40°C
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
Viscosity, kinematic	47 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LC50 - Fish [1]	> 74 mg/l Brachydanio rerio (danio rerio) - (OECD 203 method)
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna (OECD 202 method)
EC50 72h - Algae [1]	> 3 mg/l Desmodesmus subspicatus - (OECD 201 method)

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

LC50 - Fish [1]	4,5 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	5,4 mg/l Daphnia magna (water flea) OECD Test Guideline 202
EC50 96h - Algae [1]	2,1 mg/l Selenastrum capricornutum (green algae) OECD Test Guideline 201

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d)
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 1000 mg/l Pseudokirchneriella subcapitata (72h)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	< 60 % OECD 301F (28d)

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Persistence and degradability	Not biodegradable.
Biodegradation	2 – 4 % OECD 301B

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	1,5 % 28d - OECD 301 B

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Biodegradation	31 % OECD 301F (28d)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

Biodegradation	31 %
----------------	------

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3,9 – 6
---	---------

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Bioconcentration factor (BCF REACH)	260 35 D, Oncorhynchus mykiss (Rainbow trout)
-------------------------------------	---

Partition coefficient n-octanol/water (Log Pow)	9,2
---	-----

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Partition coefficient n-octanol/water (Log Pow)	0,9 @23°C
---	-----------

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

12.4. Mobility in soil

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
- Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.
- Joint storage table :
- | | | | | |
|----------|---------|----------|----------|-----------|
| LGK 1 | LGK 2A | LGK 2B | LGK 3 | LGK 4.1A |
| LGK 4.1B | LGK 4.2 | LGK 4.3 | LGK 5.1A | LGK 5.1B |
| LGK 5.1C | LGK 5.2 | LGK 6.1A | LGK 6.1B | LGK 6.1C |
| LGK 6.1D | LGK 6.2 | LGK 7 | LGK 8A | LGK 8B |
| LGK 10 | LGK 11 | LGK 12 | LGK 13 | LGK 10-13 |
- Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.
- Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.
- Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)
- Ministry's list of carcinogens : Distillates (petroleum), hydrotreated heavy paraffinic, Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate), Distillates (petroleum), solvent-dewaxed light paraffinic, Distillates (petroleum), solvent-dewaxed heavy paraffinic, Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil are listed
- Ministry's list of mutagens : Distillates (petroleum), hydrotreated heavy paraffinic, Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate), Distillates (petroleum), solvent-dewaxed light paraffinic, Distillates (petroleum), solvent-dewaxed heavy paraffinic, Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil are listed
- NON-exhaustive list of reproductive toxins - Breastfeeding : None of the components are listed
- NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed
- NON-exhaustive list of reproductive toxins - Evolution : None of the components are listed

Denmark

- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

- Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
	Flammability (solid, gas)	Added	
2.1	Adverse physicochemical, human health and environmental effects	Added	
2.2	EUH-statements	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after skin contact	Added	
4.1	First-aid measures after inhalation	Added	
4.1	First-aid measures after ingestion	Added	
4.1	First-aid measures after eye contact	Added	
5.1	Suitable extinguishing media	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Added	
6.1	Protective equipment	Added	
6.1	Emergency procedures	Added	
6.2	Environmental precautions	Added	
6.3	Methods for cleaning up	Added	
6.3	Other information	Added	
6.4	Reference to other sections (8, 13)	Added	
7.1	Precautions for safe handling	Added	
7.1	Hygiene measures	Added	
7.2	Storage conditions	Added	
8.2	Environmental exposure controls	Added	
8.2	Respiratory protection	Added	
8.2	Hand protection	Added	
8.2	Eye protection	Added	
8.2	Appropriate engineering controls	Added	
8.2	Skin and body protection	Added	
9.1	Viscosity, kinematic	Modified	
9.1	Freezing point	Modified	
9.1	Flash point	Modified	
9.1	Density	Modified	
10.1	Reactivity	Added	
10.2	Chemical stability	Added	
10.3	Possibility of hazardous reactions	Added	

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
10.4	Conditions to avoid	Added	
10.6	Hazardous decomposition products	Added	
12.1	Ecology - general	Added	
13.1	Waste treatment methods	Added	
13.1	HP Code	Added	
15.2	Chemical safety assessment	Added	
16	Abbreviations and acronyms	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)

DEX QM MOTOR 15W-40

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.